HYINTECH

HYB505U

Desktop UHF RFID Reader&Writer

USB Interface



Size: 105mmx70mmx11mm OEM, No Logo on Product is Available



General Description

HYB505U is a high performance Multiple Protocol UHF RFID Reader. It is designed upon fully self-intellectual property. Based on proprietary efficient digital signal processing algorithm, it supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as logistics, access control, attendance system, anti-counterfeit and industrial production process control system.

FEATURES

- Self-intellectual property;
- Support ISO18000-6B, ISO18000-6C(EPC C1G2) protocol tag;
- 860~928MHz frequency band(frequency customization optional);
- FHSS or Fix Frequency transmission;
- RF output power up to 10dbm(adjustable);
- No external power source needed;
- Built-in antenna with effect distance up to 200mm^{*};
- Support USB1.1 interface with VSP(Virtual Serial Port) or HID mode;
- Slim outline;
- Provide SDK and demo software to facilitate further development.

* Effective distance depends on protocol, tag and environment.

CHARACTERISTICS

• Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	6	V
Operating Temp.	T _{OPR}	-10~+60	°C
Storage Temp.	T _{STR}	-25~+80	°C

• Electrical and Mechanical Specification

Under $T_A = 25^{\circ}C$, VCC=+5V unless specified

,					
ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	4.5	5	5.5	V
Current Dissipation	Ic		120	200	mA
Frequency	F _{REQ}	860		928	MHz
Effective Distance	Dis	0	100	200	mm

* Effective distance depends on protocol, tag and environment.



DEMO SOFTWARE

SDK Include Full Demo Source Code, and full Manuals. Any further development could develop easily based on it. Any Technical Problem during your application and development, could consult our professional engineer team. Free Engineering Consultancy is one of our Outstanding After Service. Our Professional Engineer with rich experience on deployment, will leave you guidance and instruction, solving your technical problem on programming.

eader	Parameter	EPCC1-G2 Test	18000-6B Test	Frequency	/ Analysis			
List H	PC of Tags		81 	- 68	1.01	Query Tag		
No.	ID		EPCLength		Times	Read Interva	al: 50ms	• Query Tag
						Kill Tag		
								-
						Kill Passwor (8 Hex):	rd 00000000	Kill Tag
						Write EPC (Re	andom write one tag in	the antenna)
SPC Ma	ask Enabled					Write EPC: (1-15Word)	0000	
_ Ena	bled	MaskAdr: 00		MaskLen:	00	Access Passw (8 Hex):	ord 00000000	Write EPC
(ead I)ata / Write	e Data / Block	Erase			Read Protect	tion	
				•				-
🔊 Pa	ssword 🧕	EPC 🔘 TID	🔘 Vser			Access Passw (8 Hex):	word 00000000	
Addre	ss of Tag D	ata (Word/Hex) :	00				et Single Tag Read Pro	testion
Lengtl	h of Data(R	ead/Block Erase) 🖌				et bingre lag nead ito	cectron
	D/Word/D):					Set Sin	gle Tag Read Protectio	n without EPC
Acces	s Password	(8 Hex): 000000	00			Reset Si	ngle Tag Read Protecti	on without EPC
Write	Data (Hex)	: 0000						
Read	Write BI	ockWrite Blo	ckErase Cle	ar		Detect S:	ingle Tag Read Protect:	on without EPC
		Reading Or Writ				EAS Alarm		
et II	otect ror 1	reading of write	-					-
Lock	of Password	la.) EPC 🔵 TID 🔵 Vs ID and Vser Bank-	Access Passw (8 Hex):	ord 00000000	
-	10121012	101 INS	0	Writeable :	from any state	🔘 Alarm		
() K:	ill Passwor	d 🔘 Access Pas		Writeshla	from the secured s	💿 No Alarm	Alarm Setting	Check Alarm
 Readable and writeable from any state Writeable from the secured state Permanently writeable 					Lock Block for User (Permanently Lock)			
Re		writeable from	the	5		1	W/ 4504	•
2019	아파 아이에 잘 못했다.		10 10 10 10 10 10 10 10 10 10 10 10 10 1	Never write	5.0.000A	Address of (Word):	Tag Data 0 and 1	-
	100000	eadable and wri		cess Passwom		Access Pass	word	_
100 C 100	row woodshi	e and writeable	00	000000	Set Protec	(8 Hex):	00000000	Lock



eader Parame ist ID of Ta	ter EPCC1-G2 Test	18000-6B Test Fr	equency Analysis					
No. ID	462					13	Times	Ť.
NO. ID							limes	
uery Tag	15		Read and Wr	ite Data Block	/ Permanent	ly Write Protect :	Block of byt	.e
	1: 50ms		Read and Wr	ite Data Block	/ Permanent	ly Write Protect :	Block of byt	.e,
Query Tag Gead Interval				ct Address	/ Permanent	Length of	Data: 12	
ead Interval	one	Query	Start/Prote (00-E9) (Hes	ct Address			Data: 12	
ead Interval	one		Start/Prote (00-E9) (Hes	ct Address 00):	: 0000	Length of	Data: 12	
	one Condition		 Start/Prote (00-E9) (Hes Write Data 	ct Address 00): (1-32 Byte/Hex)	: 0000	Length of (1-32/Byt	Data: 12 e/D)	
dead Interval Query by d Query by (one Condition y Condition		 Start/Prote (00-E9) (Hes Write Data 	ct Address 00): (1-32 Byte/Hex)	: 0000	Length of (1-32/Byt	Data: 12 e/D)	
 Query by o Query by o Query by 0 Query Tags by Equal Conc 	one Condition y Condition dition () Une	Query equal Condition	V Start/Prote (OO-E9)(He) Write Data Read	ct Address 00): (1-32 Byte/Hex)	: 0000	Length of (1-32/Byt	Data: 12 e/D)	
ead Interval Query by (Query by (uery Tags by Equal Conc	one Condition y Condition dition () Une	Query	V Start/Prote (OO-E9)(He) Write Data Read	ct Address 00): (1-32 Byte/Hex)	: 0000	Length of (1-32/Byt	Data: 12 e/D)	
Query by o Query by o Query by (uery Tags by Equal Cond Less than	one Condition y Condition dition () Une	Query equal Condition	V Start/Prote (OO-E9)(He) Write Data Read	ct Address 00): (1-32 Byte/Hex)	: 0000	Length of (1-32/Byt	Data: 12 e/D)	

Hyintech Team

Supply You Best Products,

Free Detailed Manual and SDK

Most Professional Technical Support

Be Your Best Friend and Loyal Long Term Partner.

More Detail Please visit Our website www.hyintech.com

 $\bigoplus_{\frac{\text{www.hyintech.com}}{4}} \bigoplus_{4}$